Energies Decorator self-grounding TAMPER-RESISTANT

COMMERCIAL GRADE RECEPTACLE

MODEL NO: 62060-TR

DESCRIPTION

Commercial grade receptacles are rated for variety of standard configurations. Tamper-resistant shutters prevent foreign objects from being inserted. Each duplex is equipped with break-off plaster ears and tabs to allow for easy alignment and 2-circuit conversion. All decorator receptacles are designed with thermoplastic construction and feature a shallow build for maximum wiring room.

FEATURES	SPECIFICATIONS	
 Sturdy galvanized steel strap with a wrap- around design ensures secure assembly. Self-grounding automatically bonds to grounded metal enclosure. Durable thermoplastic build for extended use in commercial settings. Back wiring terminals accommodate solid and stranded wires for easier installation. Tamper-resistant receptacles comply with 2014 NEC[®] Article 406.12, which requires tamper-resistant 15A and 20A, 125V receptacles in dwelling units. 	Amperage Voltage NEMA Termination Material Operating Temperature Warranty	20 Amp 125 VAC 5-20R Back Wiring Thermoplastic -104° F to 167° F 2 Years
TESTING & CODE COMPLIANCE	APPLICATIONS	
LISTED		OfficesHotelsRestaurants

SPECIFICATION SUBMITTAL

